

# TETRA COMPACT- eXtreme

## PRODUCT LINEUP

Servomotor Type	Rated Output Power	Rated Torque	Peak Torque	Rated Voltage	Rated Speed	Drive Type
	[W]	[Nm]	[Nm]	[V]	[rpm]	
TC-X 40 0,16 32	60	0,19	0,48	24 Vdc	3000	-
TC -X 40 0,16 01	60	0,19	0,48	48 Vdc	3000	-
TC-X 40 0,32 01	100	0,32	0,96	48 Vdc	3000	-
TC-X 40 0,32 21	100	0,32	0,96	230 Vac	3000	FLEXI PRO 1D5 2 A
TC-X 60 0,65 21	200	0,64	1,95	230 Vac	3000	FLEXI PRO 1D5 2 A
TC-X 60 1,3 21	370	1,18	3,9	230 Vac	3000	FLEXI PRO 003 2 A
TC-X 60 1,3 15	370	1,18	3,9	400 Vac	3000	FLEXI PRO 003 4 D
TC-X 80 1,5 21	480	1,53	4,5	230 Vac	3000	FLEXI PRO 006 2 A
TC-X 80 1,5 15	480	1,53	4,5	400 Vac	3000	FLEXI PRO 003 4 D
TC-X 80 2,8 21	800	2,55	8,4	230 Vac	3000	FLEXI PRO 006 2 A
TC-X 80 2,8 15	800	2,55	8,4	400 Vac	3000	FLEXI PRO 006 4 D
TC-X 80 4 15	1068	3,4	12,0	230 Vac	3000	FLEXI PRO 006 2 A
TC-X 80 4 17	1068	3,4	12,0	400 Vac	3000	FLEXI PRO 003 4 D
TC-X 100 3,2 21	820	2,61	11,0	230 Vac	3000	FLEXI PRO 006 2 A
TC-X 100 3,2 15	820	2,61	11,0	400 Vac	3000	FLEXI PRO 006 4 D
TC-X 100 5,6 15	1320	4,2	22,0	400 Vac	3000	FLEXI PRO 012 4 A
TC-X 100 8 15	1570	5,0	33,0	400 Vac	3000	FLEXI PRO 012 4 D